

Western Fiber Company Phone: (661) 854-5556

*Performance Specifications WF-20CBB Erosion Control Blankets

100% Coco Erosion Control Blankets consist of 100% coconut fiber mechanically bound and covered on both sides by biodegradable natural fiber netting. The coconut fiber is homogeneously blended and evenly distributed throughout the blanket. The netting is biodegradable natural fiber with mesh openings of approximately .50 X 1.00 inches. The blanket is sewn on approximately 1.5 in. centers with biodegradable thread.

PROPERTY	TEST METHOD	DATA ENGLISH	
† Physical			
Mass Per Unit Area	ASTM D 6475	8.5 oz/yd²	
Thickness	ASTM D 6525	0.29 in	
† Endurance Functional Longevity	Observed	Up to 36 months	
 → Mechanical Grab Tensile Strength Grab Tensile Elongation 	ASTM D 4595	201 x 193 lb/ft 17%	
† Dimensional			
Standard Roll Size / Packaging	Measured	8 ft x 112.5 ft 100 yd² 85 lbs	

¹ A 'typical value' is the average value obtained when testing the product

Western Fiber Company
Tel: 661.854.5556* Fax: 661.854.4556
P.O. Box 22665
Bakersfield, CA 93390
www.westernfiber.com

⁺ The properties reported above are effective 02/01/07 and are subject to change without notice.

^{*}Manufactured for Western Fiber Company